

SuperSport Racing Brake Discs Th. 5,5 Applications Table

Model	Year From	To	Disc	Code	Note
APRILIA					
RSV1000, RSV1000R	2000	2003	320	208.9737.25	1,10
RSV1000R	2004	2005	320	208.9737.25	1,10
RSV1000R Factory	2004	2005	320	208.9737.25	1,10
Tuono models with axial mount calipers	2002	2005	320	208.9737.25	1,10
Tuono models with radial mount calipers	2002	2005	320	208.9737.25	1,10
DUCATI					
916	1994	2003	320	208.9737.10	10
996, 998, excluding R models	1999	2003	320	208.9737.10	10
749,999 models with axial mount calipers	2003	2005	320	208.9737.11	10
999 R/S	2003	2006	320	208.9737.11	10
Monster S4R S	2003	2005	320	208.9737.10	10
848	2008	2008	320	208.9737.11	
1098	2007	2008	320	208.9737.11	
HONDA					
VTR 1000 SP1, SP2 (RC51)	2000	2006	320	208.9737.12	10
CBR 600 RR	2003	2004	310	208.9737.13	10
CBR 600 RR	2005	2008	310	208.9737.13	10
CBR 600 RR	2005	2008	320	208.9737.12	11
CBR 1000 RR	2004	2005	310	208.9737.13	10
CBR 1000 RR	2004	2005	320	208.9737.12	11
CBR 1000 RR	2006	2006	320	208.9737.12	10
CBR 1000 RR	2007	2007	320	208.9737.12	10
CBR 1000 RR	2008	2008	320	208.9737.31	
KAWASAKI					
ZX 6 R (600 cc)	2003	2004	300	208.9737.14	3
ZX 6 R (636 cc)	2005	2006	300	208.9737.14	10
ZX 6 RR (636 cc)	2003	2004	300	208.9737.14	3
ZX 6 RR (600 cc)	2005	2007	300	208.9737.14	10
ZX 6 RR (600 cc)	2008	2008	300	208.9737.14	10
ZX 6 RR (600 cc)	2005	2007	320	208.9737.22	4
ZX 6 RR (600 cc)	2008	2008	320	208.9737.22	4
ZX 10 R	2004	2007	320	208.9737.22	4
ZX 10 R	2004	2007	300	208.9737.14	10
ZX 10 R	2008	2008	310	TBD	
ZX 10 R	2008	2008	320	208.9737.22	4
KTM					
Supermoto 950	2005	2008	320	208.9737.10	
990 Superduke	2007	2008	320	208.9737.10	
RC8	2008	2008	320	208.9737.11	10
MV AGUSTA					
F4 750 S	2003	2007	310	208.9737.27	10
F4 -1000 S	2005	2007	310	208.9737.27	10
F4- 1000 R & Senna	2006	2007	320	208.9737.28	10
Brutale S	2004	2005	310	208.9737.27	10
Brutale 910	2006	2007	310	208.9737.27	10
Brutale R	2006	2007	320	208.9737.28	10

SuperSport Racing Brake Discs Th. 5,5 Applications Table

Model	Year From	To	Disc	Code	Note
SUZUKI					
GSX-R 600	2001	2003	320	208.9737.15	10
GSX-R 600	2004	2005	300	208.9737.16	10
GSX-R 600	2006	2007	310	208.9737.17	10
GSX-R 600	2008	2008	310	208.9737.32	
GSX-R 600	2006	2007	320	208.9737.26	5
GSX-R 600	2008	2008	320	208.9737.33	
GSX-R 750	2000	2003	320	208.9737.15	10
GSX-R 750	2004	2005	300	208.9737.16	10
GSX-R 750	2006	2007	310	208.9737.17	10
GSX-R 750	2006	2007	320	208.9737.26	5
GSX-R 1000	2001	2002	320	208.9737.15	10
GSX-R 1000	2003	2004	300	208.9737.16	10
GSX-R 1000	2005	2008	310	208.9737.17	10
GSX-R 1000	2005	2008	320	208.9737.26	5
Hayabusa	1999	2005	320	208.9737.15	10
Hayabusa	2008	2008	310	TBD	
TRIUMPH					
Speed Triple	2004	2005	320	208.9737.23	10
675	2008	2008	310	208.9737.30	
YAMAHA					
YZF-R6	1999	2002	300	208.9737.18	
YZF-R6	2003	2004	300	208.9737.19	
YZF-R6	2005	2007	310	208.9737.20	10
YZF-R6	2008	2008	310	208.9737.20	10
YZF-R6	2005	2007	320	208.9737.21	12
YZF-R6	2008	2008	320	208.9737.21	12
YZF-R6S	2006	2006	300	208.9737.19	10
YZF-R1	1998	2003	300	208.9737.18	10
YZF-R1	2004	2005	320	208.9737.21	10
YZF-R1	2006	2006	320	208.9737.21	10
YZF-R1 SP-LE	2006	2006	320	208.9737.24	10
YZF-R1	2007	2008	310	208.9737.20	10
YZF-R1	2007	2008	320	208.9737.21	

Specific Notes:

- 1 - Aprilia applications require new disc mounting bolts, available into the disc kit.
- 2 - OEM disc diameter is 320 mm., 310 mm. discs (208.9737.13) may be used by removing the spacers under the brake caliper.
- 3 - OEM disc diameter is 280 mm., 300 mm. discs (208.9737.14) may be used by adding the spacers under the brake caliper.
- 4 - OEM disc diameter is 300 mm., 320 mm. discs (208.9737.22) may be used by adding the spacers under the brake caliper.
- 5 - OEM disc diameter is 310 mm., 320 mm. discs (208.9737.26) may be used by adding the spacers under the brake caliper.
- 10 - Discs with ABE approval granted by the German Ministry of Transport on TÜV certification.
- 11 - OEM disc diameter is 310 mm., 320 mm. discs (208.9737.12) may be used by adding the spacer under the OEM.
- 12 - OEM disc diameter is 310 mm., 320 mm. discs (208.9737.21) may be used by adding the spacer under the OEM.

Note:

- 1 - Le applicazioni Aprilia richiedono nuove viti per il fissaggio, comunque contenute nel kit
- 2 - Il disco originale è ø 320 mm. Si possono utilizzare dischi ø 310 mm. (cod. 208.9737.13) rimuovendo i distanziali sotto le pinze.
- 3 - Il disco originale è ø 280 mm. Si possono utilizzare dischi ø 300 mm. (cod. 208.9737.14) aggiungendo dei distanziali sotto le pinze.
- 4 - Il disco originale è ø 300 mm. Si possono utilizzare dischi ø 320 mm. (codice 208.9737.22) aggiungendo dei distanziali sotto le pinze.
- 5 - Il disco originale è ø 310 mm. Si possono utilizzare dischi ø 320 mm. (cod. 208.9737.26) aggiungendo dei distanziali sotto le pinze.
- 10 - Disco con ABE, certificato TÜV
- 11 - Il disco originale è ø 310 mm. Si possono utilizzare dischi ø 320 mm. (codice 208.9737.12) aggiungendo dei distanziali sotto le pinze.
- 12 - Il disco originale è ø 310 mm. Si possono utilizzare dischi ø 320 mm. (codice 208.9737.21) aggiungendo dei distanziali sotto le pinze.